



KCU6A4PZH D

Cat.6a cable U/UTP LSZH Dca 4 pairs



- | | |
|-------------------------|-----------------------------------------|
| 1. Conductor : AWG23 | 3. Filler : PE cross |
| 2. Insulation: Solid PE | 4. Jacket : LSZH Light blue
RAL 5024 |

UNIK ✓

- ✓ Compliant to ISO 11801 Class Ea
- ✓ Jacket LSZH Dca EN50575
- ✓ Tested up to 500 MHz

THE PURPOSE

The Unikkern Cat6a U/UTP cable AWG 23, rigorously tested to TIA/EIA 568.D-2 and ISO/IEC 11801 Cat6a standards, ensures dependable performance for copper infrastructure. Available in 305m and 500m lengths, it supports link performance up to 90m thanks to Unikkern's advanced assembly technology, making it appropriate for 1G BASE T, 2.5G BASE T, and 5G BASE T applications. Encased in an LSZH sheath that meets CPR Euroclass Dca, this cable is distinguished by its flexibility and smaller outer diameter, facilitating installation in spaces where space is at a premium.

COMPLIANCE

Cable standard

IEC 60156-5:2020 Cat6a

System

ISO/IEC 11801-1:2017 Class Ea
TIA 568.2-D Cat6a

Applications

IEEE 802.3 : 1G, 2,5G & 5G BASE T
IEEE 802.3 POE : Type 1 & 4, up to 90w

THE STRUCTURE

Conductor : Solid copper AWG23

Insulation : Solid polyethylen 1.0+/- 0,05mm

Color coding : Blue/White-blue, Orange/white-orange, Green/White-green, Brown/White-brown

Assembly : Polyethylen minicross filler

Jacket : LSZH Light Blue RAL 5024

Marking : UNIKKERN DATA CABLE U/UTP CAT6A 4 PAIRS AWG23 100OHM 500MHZ NVP 75% EN50575 Dca-
IEC 61156-5/ISO11801/TIA-EIA 568.2-D CE LSZH xxxxxxM



KCU6A4PLZHDx

Cat.6a cable U/UTP LSZH Dca 4 pairs




TECHNICALITIES

- Loop resistance (DC max) at 20°C : 93.8 Ω/Km
- Insulation resistance (min) : 5 GΩ*Km
- Mutual capacitance : 56+/- 5 nF/Km
- Capacitance unbalance at 1khz (pair to ground) : 1600 pF/Km
- Resistance unbalance (pair to pair) : 2%
- Nominal voltage : 150V
- Voltage Test : AC 50hz : 700V / DC : 1000V
- Characteristic Impedance at 100 Mhz : 100 ohms+/- 5%
- Nominal velocity propagation : 75%
- Fire behavior : IEC 60332-1

PURCHASE INFO

Category	Shielding	Item	Designation	Diameter (nom)	Weight (kg/Km)	Packing
Cat.6a	U/UTP	KCU6A4PLZHDBL5	Cat.6a cable 4 pairs U/UTP awg23 LSZH Dca	6.3 mm	37	D500M
Cat.6a	U/UTP	KCU6A4PLZHDBLB	Cat.6a cable 4 pairs U/UTP awg23 LSZH Dca	6.3 mm	37	B305M

EXTRAS



KJ6AUHQx

Cat6a keystone jack unshielded



KJPP1UBCTEF

Patch panel 1U 24 ports RJ45



www.unikkern.com

This confidential Syskern datasheet cannot be altered or reproduced without written permission. Its specifications are subject to change without notice.

Cette fiche technique confidentielle de Syskern ne peut être modifiée ou reproduite sans permission écrite. Ses spécifications peuvent changer sans préavis